

COPAR **Panzer**


The Popular T65 Series

MORE Than a RIDING MOWER
America's
FINEST GARDEN TRACTOR




Exclusive Features:


- **Glidematic** No Clutch Transmission
- **Floating** Power Vibration Free Ride
- Independent Rear Wheel Brakes
- Genuine Automotive Differential




Rotary Mower 11AC9
35" wide cut, adjustable cutting height up to 4", cuts outside both tractor wheels, floating, anti-scalping skids, removable anti-windrow baffle. (Note: Rewires Model 52PT Power Take-Off Kit)




Power Take-Off Kit 52PT
Positive engage and disengage clutch. (Required for 11AC9 Rotary Mower)



Power Driven Spreader PS1
36" wide coverage, adjustable feed, on and off handle, adjustable hopper heights. Capacity - 180 lbs. May be used simultaneously with Rotary to mark and spread. Model 2AC2 Rear Lift required.



Front Utility Box 4AC4
Handy utility carrier. Convenient for adding weight to front end of tractor for heavy pulling jobs, plowing or snowplowing.




Front Utility Rack 4AC5
Handy utility carrier. Convenient for adding weight to front end of tractor for heavy pulling jobs, plowing or snowplowing.




Fenders TAM
Strong, durable, heavy-duty fenders. Protects operator from dirt, mud, stones.


and with these
ATTACHMENTS!




Plow 1AC5
8" moldboard plow. Adjustable depth. Spring loaded for easy lifting. Model 2AC2 Rear Lift required.




Cultivator 3AC2
Six tooth cultivator. Fully adjustable for height, depth, and spread. Model 2AC2 Rear Lift required.




Rear Lift 2AC2
Required to connect 1AC5 Plow, 3AC2 Cultivator and PS1 Spreader to tractor lift handle.




Disc Harrow 6AC2
Two fully adjustable gangs, of four 12" discs. 33" coverage.




Spike Tooth Harrow TH1
Eighteen tooth spike tooth harrow. Teeth adjustable as to angle.




Reel Mower Unit (Std. wheel) TGR1
Reel Mower Unit (Wide wheel) TGR2
60" wide cut, adjustable cutting height.



Snowplow Blade 10AC4
42" blade adjustable in either direction. Blade can be angled to any one of five positions. Raised or lowered by tractor lift handle.



Roller S-R01
18" x 24" roller, weight filled with water 300 pounds.



Dump Cart S-DT1
All steel 24" x 36" dump unit.

The perfect combination mower-tractor! Out-performs all riding mowers with its 35" cut, height adjustment to a full 4", smoother, safer big wheel floatation that can't bog down. Outlasts other equipment because it's built like a tractor. Big tractor performance with quick-hitch attachments for snowplowing, plowing, cultivating, spreading and... all other lawn and garden chores.

SPECIFICATIONS

5 3/4 HP Briggs & Stratton Engine with recoil starter and Choke-A-Matir ● Beautiful aqua finish with white trim ● Glidematic Drive ● Floating Power Ride ● Two forward speeds and one reverse ● 6-12 Rear tires ● 4.10/3.50-6 Front tires ● Length 58" ● Width 34" ● Weight 400 lbs. ● Automotive Differential rear end ● Independent rear brakes.